Overview

HP 355 G2 Notebook PC



1. WLAN antennas
2. Internal microphones
3. Webcam LED
4. HP HD Webcam
5. Finger print reader (select models only)
6. Right TouchPad button
7. Left TouchPad button
8. Touchpad with scroll zone
9. SD Card reader
10. USB 3.0 ports (2)
11. RJ-45 (Ethernet)
12. HDMI port
13. VGA port
14. AC Plug LED
15. Power connector
16. Power button

Overview



1. Duplicate power LED
2. Hard drive LED
3. Headphone / Microphone in Combo Jack
4. USB 2.0 Port
5. Optical drive button
6. Security cable slot

Overview

AT A GLANCE

- Windows 8.1 versions, Windows 7 Professional 64 (available through downgrade rights from Windows 8.1 Pro 64), Ubuntu Linux, FreeDOS 2.0
- AMD Radeon™ R5 M240 discrete graphics (1 GB or 2 GB DDR3, Switchable Graphics)
- Durable, sophisticated design with smooth surfaced silver color.
- Full-sized keyboard with numeric keypad
- Spill-resistant keyboard and HP 3D Drive Guard protects your system from accidental spills or drops
- HDMI port for connecting to high-resolution displays
- Integrated HP HD Webcam, integrated microphone
- 802.11 b/g/n 1x1 wireless LAN module, 802.11 b/g/n 1x1 wireless LAN module + Bluetooth® 4.0 combo, and 802.11 a/b/g/n 2x2 wireless LAN module + Bluetooth® 4.0 combo
- 15.6" diagonal LED-backlit HD anti-glare (1366 x 768)

NOTE: See important legal disclosures for all listed specs in their respective features sections.

Features

PRODUCT NAMES

HP 355 G2 Notebook PC

OPERATING SYSTEM

Preinstalled

Windows 8.1*
Windows 8.1 Pro*
Windows 7 Professional 64 (available through downgrade rights from Windows 8.1 Pro 64**)
Ubuntu Linux
FreeDOS 2.0

* Not all features are available in all editions of Windows 8.1. Systems may require upgraded and/or separately purchased hardware, drivers and/or software to take full advantage of Windows 8.1 functionality. See http://www.microsoft.com for details.
** This system is preinstalled with Windows® 7 Pro software and also comes with a license and media for Windows 8.1 Pro software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

ACCELERATED PROCESSING UNIT

AMD
AMD A8-6410 APU (2.0GHz, 2MB L2 cache, 4 core)* with AMD Radeon™ R5 Graphics
AMD A6-6310 APU (1.8 GHz/2.4 GHz, 2 MB L2 cache, 4 cores)* with AMD Radeon™ R4 Graphics
AMD A4-6210 APU (1.8 GHz, 2 MB L2 cache, 4 cores)* with AMD Radeon™ R3 Graphics
AMD E2-6110 APU (1.5 GHz, 2 MB L2 cache, 2 cores)* with AMD Radeon™ R2 Graphics
AMD E1-6010 APU (1.35 GHz, 1 MB L2 cache, 2 cores)* with AMD Radeon™ R2 Graphics

*This system requires a separately purchased 64-bit operating system and 64-bit software products to take advantage of the 64-bit processing capabilities of AMD technology. Multi-core processing with AMD technology is designed to improve performance of this system. Given the wide range of SW applications available, performance will vary. AMD's numbering is not a measurement of clock speed.

CHIPSET

AMD Chipset is integrated with APU

GRAPHICS

Integrated:
AMD Radeon™ R5 Graphics (AMD A8-6410 APU)
AMD Radeon™ R4 Graphics (AMD A6-6310 APU)
AMD Radeon™ R3 Graphics (AMD A4-6210 APU)
AMD Radeon™ R2 Graphics (AMD E2-6110 APU and AMD E1-6010 APU)

Discrete:
AMD Radeon™ R5 M240Graphics with up 2048MB of dedicated video memory (Switchable Graphics)

DISPLAY

Features

Internal
15.6" diagonal LED-backlit HD anti-glare (1366 x 768)
External
Up to 32-bit per pixel color depth
VGA
Port supports resolutions up to 1080p, 1920 x 1080 at 60Hz
HDMI*
1.4 port supports up to 1080p, 1920 x 1080 at 60Hz

*HDMI cable sold separately.
NOTE: Resolutions are dependent upon monitor capability, and resolution and color depth settings.

STORAGE AND DRIVES

Primary Storage Bay
Hard Drives
500/750 GB/1 TB 5400 rpm SATA
500 GB 7200 rpm SATA

NOTE: For hard drives, GB = 1 billion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 8.1) of system disk is reserved for the system recovery software.

OPTICAL DRIVES

Fixed Optical Drive
DVD+/-RW SuperMulti DL* Drive
Weight Saver option

* * Double-layer discs can store more data than single layer discs. However, double-layer discs burned with this drive may not be compatible with many existing single-layer DVD drives and players. Note that this drive cannot read or write to 2.6 GB single-sided/5.2 GB double-sided – version 1.0 media. Don't copy copy-right protected materials.

MEMORY

Standard
DDR3L SDRAM (1600 MHz)
Two SODIMM slots supporting dual-channel memory
Standard memory up to 8192 MB*
Maximum
Upgradeable to 16384 MB
Dual-channel
Maximized dual-channel performance requires SODIMMs of the same size and speed in both memory slots.

NOTE: Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

***** Maximum memory capacities assume Windows 64-bit operating systems or Linux. With Windows 32-bit operating systems, memory above 3 GB may not all be available due to system resource requirements.

NETWORKING/COMMUNICATIONS

Features

Wireless
802.11 b/g/n (1x1) wireless LAN module[1,2]
802.11 b/g/n (1x1) + Bluetooth 4.0 Combo[1,2]
802.11 a/b/g/n (2x2) + Bluetooth 4.0 Combo[1,2]

Communications
Realtek Gigabit Network Connection (10/100/1000 NIC)

1. Sold separately or as an optional feature.
2. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited.

AUDIO/MULTIMEDIA

Audio
DTS Sound
Integrated Stereo Speaker
Headphone / Microphone in Combo Jack
Integrated microphone

Webcam
HP HD* Webcam**

- Supports videoconferencing and still image capture
- Improved quality for video streaming and still image capture (1280x720 resolution)
- Up to 30 frames/sec
- Fixed focus lens

* HD content required to view HD images.
** Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited.

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard
The 101/102-key compatible keyboard features a full-pitch key layout with desktop keyboard features, such as editing keys, both left and right control and alt keys, and function keys. US and International key layouts are available. Includes a separate numeric keypad.

Pointing Devices
Touchpad with 2-piece pick button with left and right click functions
Multi-touch gestures supported

Buttons and Function Keys
On/off button

SOFTWARE AND SECURITY

Preinstalled Software with Windows Operating System
Buy Office
Recovery Manager Installer
Cyberlink Youcam DE

Features

Cyberlink Power DVD (available on select models)
McAfee Internet Security 2013*
Getting Started with Windows 8.1

Security
Security Lock slot (lock must be purchased separately)
Fingerprint Reader (select models only)

For more information on HP security solutions refer to: http://www.hp.com/go/security.

* Internet access required. First 60 days included. Subscription required for live updates afterwards.

POWER

Power Supply
External 45W AC adapter (UMA only)
External 65W HP AC adapter 3-wire plug 1.0m (with ground pin)

Primary Battery
HP 4-cell (41 WHr) Li-Ion battery

Battery life

4-cell (41 WHr) battery	Up to TBD hours (With Windows 7)

System Standby Time
Up to 1 week*

*Standby life will vary depending on various factors including battery, Memory, CPU, EC and LAN chip. The maximum capacity of the battery will naturally decrease with time and usage.

Power Conservation
Hibernation*
Standby*
ACPI compliance*

* Only Linux will feature power conservation.

WEIGHTS & DIMENSIONS

Weight
Starting at 5.07 lbs (2.30 kg)
Weight will vary by configuration.

Dimensions (w x d x h)
10.28 x 15.12 x .91 in
26.1 x 38.4 x 2.31 cm

NOTE: Height varies depending upon where on the notebook the measurement is made. Weight varies by configuration and components.

Features

PORTS/SLOTS

Ports
VGA – One
HDMI* – One
Headphone / Microphone in Combo Jack – One
Power Connector – One
RJ-45 (Ethernet) - One
USB 3.0 – Two
USB 2.0 – One

Expansion Slots
HP Multi-Format Digital Media Reader - supports SD/SDHC/SDXC
Supports mini versions with adapter

* HDMI cable sold separately.

SERVICE AND SUPPORT

HP Services offers limited 1-year warranty options depending on country;
1-year limited warranty on primary battery. On-site service and warranty upgrades are also available. Optional* HP Care Pack Services** are extended service contracts which go beyond your standard warranties. For more details visit: http://www.hp.com/go/lookuptool.

*Sold separately or as an optional feature.
** Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. Consult the HP Customer Support Center for details. http://h20000.www2.hp.com/bizsupport/TechSupport/ProductRoot.jsp

Technical Specifications

SYSTEM UNIT

Stand-Alone Power Requirements (AC Power)	**Nominal Operating Voltage**	18.5/19.5V
	Average Operating Power	Integrated graphics: TBD W
	Max Operating Power	< 65 W
Temperature	**Operating**	32° to 95° F (0° to 35° C) (not writing optical) 41° to 95° F (5° to 35° C) (writing optical)
	Non-operating	-4° to 140° F (-20° to 60° C)
Relative Humidity	**Operating**	10% to 90%, non-condensing
	Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature
Shock	**Operating**	40 G, 2 ms, half-sine
	Non-operating	200 G, 2 ms, half-sine
Random Vibration	**Operating**	0.75 grms
	Non-operating	1.50 grms
Altitude (unpressurized)	**Operating**	-50 to 10,000 ft (-15.24 to 3,048 m)
	Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)
Planned Industry Standard Certifications	**UL**	Yes
	CSA	Yes
	FCC Compliance	Yes
	ENERGY STAR®	Select models*
	EPEAT®	Registered Silver in United States**
	ICES	Yes
	Australia / NZ A-Tick Compliance	Yes
	CCC	Yes
	Japan VCCI Compliance	Yes
	KC	Yes
	BSMI	Yes
	CE Marking Compliance	Yes
	BNCI or BELUS	Yes
	CIT	Yes
	GOST	Yes
	Saudi Arabian Compliance (ICCP)	Yes
	SABS	Yes
	UKRSERTCOMPUTER	Yes

* Configurations of the HP 355 G2 Notebook PC that are ENERGY STAR qualified are identified as HP 355 G2 Energy Star on HP websites and on www.energystar.gov.
** EPEAT registration varies by country. See www.epeat.net for registration status by country.
EPEAT status listed above applies to U.S.

For accessibility information on HP products, please visit: http://www.hp.com/accessibility.

Technical Specifications

DISPLAY

15.6" diagonal LED-backlit HD anti-glare flat (1366 x 768)	**Active Area** (w x h)	13.54 x 7.59 in (34.4 x 19.4 cm)	
	Diagonal Size	15.6 in (39.6cm)	
	Surface Treatment	Anti-glare	
	Contrast Ratio	300:1 (min)	
	Refresh Rate	60 Hz	
	Brightness	200 nit (typical)	
	Pixel Resolution	**Pitch**	0.252 mm
		Format	1366 x 768
		Configuration	RGB Stripe
	Backlight	LED	
	PPI	101 ppi	
	Viewing Angle	±40° Horizontal, +10°/-30° Vertical (minimum) 40/40/30/10 (Left/Right/Down/Up) (minimum	

STORAGE AND DRIVES

Internal Storage

500 GB* 7200 rpm SATA Hard Drive	**Drive Weight**	0.25 lb (115g)	
	Capacity	500 GB	
	Height	0.276 in (7 mm)	
	Width	2.75 in (70 mm)	
	Interface	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ	
	Transfer Rate	**Synchronous** (maximum)	300 MB/s (Drive Capability)
	Seek Time (typical reads, including settling)	**Single Track**	1.5 ms
		Average	11 ms
		Maximum	22 ms
	Rotational Speed	7200 rpm	
	Logical Blocks	976,773,168	
	Operating Temperature	32° to 140° F (0° to 60° C) [case temp]	
	Features	ATA Security	

1 TB* 5400 rpm SATA Hard Drive	**Drive Weight**	0.254 lb (115 g)	
	Capacity	1 TB	
	Height	0.37 in (9.5 mm)	
	Width	2.75 in (70 mm)	
	Interface	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ	
	Transfer Rate	**Synchronous** (maximum)	300 MB/s (Drive Capability)
	Seek Time (typical reads, including settling)	**Single Track**	3 ms
		Average	13 ms
		Maximum	24 ms

Technical Specifications

	Rotational Speed	5400 rpm	
	Logical Blocks	1,953,525,168	
	Operating Temperature	32° to 140° F (0° to 60° C) [case temp]	
	Features	ATA Security	
750 GB* 5400 rpm SATA Hard Drive	**Drive Weight**	0.22 lb (101 g)	
	Capacity	750 GB	
	Height	0.37 in (9.5 mm)	
	Width	2.75 in (70 mm)	
	Interface	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ	
	Transfer Rate	**Synchronous** (maximum)	300 MB/s (Drive Capability)
	Seek Time (typical reads, including settling)	**Single Track**	3 ms
		Average	13 ms
		Maximum	24 ms
	Rotational Speed	5400 rpm	
	Logical Blocks	1,465,149,168	
	Operating Temperature	32° to 140° F (0° to 60° C) [case temp]	
	Features	ATA Security	
500 GB* 5400 rpm SATA Hard Drive	**Drive Weight**	0.22 lb (101 g)	
	Capacity	500 GB	
	Height	0.37 in (9.5 mm)	
	Width	2.75 in (70 mm)	
	Interface	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ	
	Transfer Rate	**Synchronous** (maximum)	150 MB/s (Drive Capability)
	Seek Time (typical reads, including settling)	**Single Track**	3 ms
		Average	13 ms
		Maximum	24 ms
	Rotational Speed	5400 rpm	
	Logical Blocks	976,773,168	
	Operating Temperature	32° to 140° F (0° to 60° C) [case temp]	
	Features	ATA Security	

* For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 8.1) of system disk is reserved for the system recovery software.

Optical Drives			
DVD+/-RW SuperMulti DL Drive	**Access Times**	Random	<140ms CD (typical) < 160 ms DVD (typical)
	Max Data Transfer Rate	24X CD-ROM 8X DVD 24X CD-R 24X CD-RW 8X DVD+R 8X DVD+RW 8X DVD-R 6X DVD-RW 5X DVD-RAM	
	Transfer Mode	UDMA Mode 5	
	Interface	Gen 1 SATA	
	Supported Media (read)	CD-DA, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW, DVD-RAM	
	Supported Media (write)	CD-R, CD-RW, DVD+R, DVD+RW, DVD-R, DVD-RW, DVD-RAM, DVD+R DL, DVD-R DL	
	Max Media Capacity (read)	8.5 GB	
	Max Media Capacity (write)	8.5 GB	
	Transport	Tray Loading	

NETWORKING/COMMUNICATIONS

Networking		
Integrated Realtek 10/100/1000 NIC	**Ethernet Features**	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 1000 Mbit/s operation (100BASE-T; IEEE 802.3ab; IEEE 802.3 clauses 21-30) (Support in RTL8161FH-CG only) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s IEEE 802.1p QoS (Quality of Service) Support IEEE 802.1q VLAN support IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable

Technical Specifications

	Power Management	ACPI compliant - multiple power modes Situation-sensitive features reduce power consumption Advanced link down power saving for reducing link down power consumption
	Performance Features	TCP/IP/UDP Checksum Offload (configurable) Large send offload and Giant send offload Receiving Side Scaling
	Manageability	Wake-on-LAN from standby and hibernation (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only) PXE 2.1 Remote Boot Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite Virtual Cable Doctor for Ethernet cable status
	Interface	PCI Express 1.1 x1 to fully support ASPM L0s/L1 and CLKREQ
	NIC Device Driver Name	Realtek PCIe FE Ethernet Family Controller
Communications		
**Atheros 802.11b/g/n WiFi Adapter*, **	**Wireless LAN Standards**	IEEE 802.11b IEEE 802.11g IEEE 802.11n
	Interoperability	Wi-Fi certified
	Frequency Band	2.402 - 2.482 GHz
	Data Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n150Mbps for MCS7
	Frequency Support	20 MHz: 2.4 GHz bands
	Modulation	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM, BPSK, QPSK, 16-QAM, 64-QAM
	Security[1]	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST. Support for Cisco Security Features (proven compatibility with Cisco Aironet infrastructure products through the Cisco Compatible Extensions Program Version 5) with Microsoft Windows 7only.
	Sub-channels	Multinational support with frequency bands and channels compliant to local regulations.
	Media Access Protocol	CSMA/CA (Collision Avoidance) with ACK
	Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	Roaming	IEEE 802.11 compliant roaming between access points
	Output Power[2]	13.5 dBm, minimum
	Power Consumption	Idle associated: 250 mW avg (CLKREQ enabled) Idle unassociated: 100 mW avg Transmit/Receive channel: 2.0 /1.6 W
	Power Management	ACPI compliant power management 802.11 compliant power saving mode

Receiver Sensitivity[3]	11b:-88dBm@11 Mbps, 11g:-74 dBm@54 Mbps, 11n:-70dBm@72 Mbps	
Antenna type	High efficiency dual antenna with spatial diversity, usually mounted in the display enclosure	
Form Factor	PCI-Express Half-MiniCard	
Weight	4 g	
Dimensions	3.3 x 26.65 x 29.85 mm	
Operating Voltage	3.3v +/- 9%	
Temperature	Operating	-10° to 70° C
	Non-operating	-40° to 80° C
Humidity	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
Altitude	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)
LED Activity	Amber LED on-Radio OFF; White LED on-Radio ON	

1. Check latest software/driver release for updates on supported security features.
2. Maximum output power may vary by country according to local regulations.
3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CCK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

NOTE: WLAN supplier's client utility is required for Cisco Compatible Extensions support with Microsoft Windows XP. WLAN may also be compatible with certain third-party software supplicants. WLAN supplier IHV extensions required for Cisco Compatible Extensions support for Microsoft Windows Vista and Win7.

* Wireless access point and internet service required. Availability of public wireless access points limited.

** Sold separately or as an optional add-on feature.

Ralink 802.11b/g/n Bluetooth 4.0 Combo Card*, **

Wireless LAN Standards	IEEE 802.11b IEEE 802.11g IEEE 802.11n
Interoperability	Wi-Fi certified)
Frequency Band	2.402 – 2.482 GHz
Data Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: 150Mbps for MCS7
Modulation	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM, BPSK, QPSK, 16-QAM, 64-QAM
Security[1]	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST. WAPI Support for Cisco Security Features (proven compatibility with Cisco Aironet infrastructure products through the Cisco Compatible Extensions Program Version 5) with Microsoft Windows Vista and XP only.

Technical Specifications

Sub-channels	Multinational support with frequency bands and channels compliant to local regulations.	
Media Access Protocol	CSMA/CA (Collision Avoidance) with ACK	
Network Architecture	Ad-hoc (Peer to Peer)	
Models	Infrastructure (Access Point Required)	
Roaming	IEEE 802.11 compliant roaming between access points	
Output Power (for CCK)[2]	13.5dBm , minimum	
Power Consumption	Idle associated: 250 mW Idle unassociated: 150 mW Transmit: 2.0 W (max) Receive: 2.0 W (max)	
Power Management	ACPI compliant power management 802.11 compliant power saving mode	
Receiver Sensitivity[3]	11b:-88dBm@11Mbps, 11g:-74 dBm@54Mbps, 11n:-70dBm@72.Mbps.	
Antenna type	High efficiency dual antenna with spatial diversity, mounted in the display enclosure	
Form Factor	PCI-Express Half-MiniCard v1.2	
Weight	6 g	
Dimensions	3.3 x 26.65 x 29.85 mm	
Operating Voltage	3.3v +/- 10%	
Temperature	Operating	14° to 149° F (-10° to 65° C)
	Non-operating	-40° to 176° F (-40° to 80° C)
Humidity	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
Altitude	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)
LED Activity	LED Off – Radio OFF; Solid LED On – RadioON	

1. Check latest software/driver release for updates on supported security features.
2. Maximum output power may vary by country according to local regulations.
3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CCK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

NOTE: WLAN supplier's client utility is required for Cisco Compatible Extensions support with Microsoft Windows XP. WLAN may also be compatible with certain third-party software supplicants. WLAN supplier IHV extensions required for Cisco Compatible Extensions support for Microsoft Windows Vista and Win7.

Bluetooth Specification	
V4.0 High Speed, V2.1+EDR, backwards compatible with V1.1, 1.2 and 2.0	
Number of Available Channels	79 (1 MHz) available channels
Data Rates and Throughput	3 Mbps data rate; throughput up to 2.17 Mbps
	Synchronous Connection Oriented links up to 3, 64 kbps, voice channels
	Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric or 1306.9 kbps symmetric

Technical Specifications

Transmit Power	-6 dBm to 4 dBm (Bluetooth Class II)
Receiver Sensitivity	Better than -80 dBM at 0.1 % raw bit error rate
Power Consumption	Peak (Tx) 330 mW Peak (Rx) 230 mW Sleep <17 mW
Antenna	Internally integrated within module
Range	Up to 33 ft (10 m)
Electrical Interface	USB 2.0 compliant Microsoft Windows Plug and Play compliant
Bluetooth Software Supported	Broadcom Bluetooth for Windows Microsoft Windows Bluetooth Software
Link Topology	Point to Point, Multipoint Pico Nets up to 7 slaves
Security	Full support of Bluetooth Security Provisions
Power Management	Microsoft Windows ACPI, and USB Bus Support Self configurable to optimize power conservation in all operating modes, including Standby, Hold, Park, and Sniff
Certifications	All necessary regulatory approvals for supported countries, including: FCC (47 CFR) Part 15C, Section 15.247 & 15.249 ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark
Bluetooth Profiles Supported	Generic Access Profile (GAP) Service Discovery Application Profile (SDAP) Serial Port Profile (SPP) Dial_Up Networking Profile (DUN) Generic Object Exchange Profile (GOEP) Object Push Profile (OPP) File Transfer Profile (FTP) Synchronization Profile (SYNC) Hard Copy Cable Replacement (HCRP) Personal Area Networking Profile (PAN) Human Interface Device Profile (HID) Generic Audio/Video Distribution Profile (GAVDP) Advanced Audio/Video Distribution Profile (A2DP) FAX Profile (FAX) Basic Imaging Profile (BIP) Headset Profile (HSP) Hands Free Profile (HFP) Basic Printing Profile (BPP) VDP (Video Distribution Profile) AVRCP (Audio Video Remote Control Profile)

* Wireless access point and internet service required. Availability of public wireless access points limited.
** Sold separately or as an optional add-on feature.

Broadcom 802.11 a/b/g/n (2x2) with Bluetooth® v4.0 combo*	**Wireless LAN Standards**	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n
	Interoperability	Wi-Fi certified

Technical Specifications

Frequency Band

802.11b/g/n

- 2.402 - 2.482 GHz

802.11a/n

- 4.9 - 4.95 GHz (Japan)
- 5.15 - 5.25 GHz
- 5.25 - 5.35 GHz
- 5.47 - 5.725 GHz
- 5.825 - 5.850 GHz
- 2.402 - 2.482 GHz

Data Rates

802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11b: 1, 2, 5.5, 11 Mbps
802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11n: card will support rates for NSS=1 and NSS=2 for RX and TX for 20 and 40 MHz channels. Short and long guard interval shall be supported.

Modulation

Direct Sequence Spread Spectrum
BPSK, QPSK, CCK, 16-QAM, 64-QAM

Security[1]

- IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only
- AES-CCMP: 128 bit in hardware
- 802.1x authentication
- WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.
- WPA2 certification
- IEEE 802.11i
- Cisco Certified Extensions, all versions through V5
- WAPI

Network Architecture Models

Ad-hoc (Peer to Peer)
Infrastructure (Access Point Required)

Roaming

IEEE 802.11 compliant roaming between access points

Output Power[2]

- 2.4G: +13.5dBm minimum
- 5G: +12dBm minimum
- Maximum output power must be able to achieve modular regulatory certification with notebooks that have antennas >20cm from the user and peak gain of +3dBi at 2.4GHz and +4dBi at 5GHz

Power Consumption

Transmit: 2.0 W (max)
Receive: 1.6 W (max)
Idle mode (PSP): 250 mW (WLAN Associated)
Idle mode: 100 mW (WLAN unassociated)
Radio disabled: 75 mW

Technical Specifications

Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode	
Receiver Sensitivity[3]	802.11b:-95 dBm (1 Mbps), -93 dBm (2 Mbps), -91 dBm (5.5 Mbps), -88 dBm (11 Mbps) 802.11a/g:-90 dBm (6 Mbps), -89 dBm (9 Mbps), -87 dBm (12 Mbps), -85 dBm (18 Mbps), -82 dBm (24 Mbps), -79 dBm (36 Mbps), -76 dBm (48 Mbps), -74 dBm (54 Mbps) 802.11n:-69 dBm (72.2 Mbps), -66 dBm (300 Mbps)	
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications	
Form Factor	PCI-Express Half-MiniCard	
Dimensions	0.19 x 1.06 x 1.18 in (4.75 x 26.8 x 30 mm)	
Weight	3.3g	
Operating Voltage	3.3v +/- 9%	
Temperature	Operating Non-operating	14° to 158° F (-10° to 70° C) -40° to 176° F (-40° to 80° C)
Humidity	Operating Non-operating	10% to 90% (non-condensing) 5% to 95% (non-condensing)
Altitude	Operating Non-operating	0 to 10,000 ft (3,048 m) 0 to 50,000 ft (15,240 m)
LED Activity	LED Off - Radio OFF; Solid LED On - Radio ON	

1. Check latest software/driver release for updates on supported security features.
2. Maximum output power may vary by country according to local regulations.
3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

Bluetooth Specification

V4.0 High Speed, V2.1+EDR, backwards compatible with V1.1, 1.2 and 2.0

Number of Available Channels	79 (1 MHz) available channels
Data Rates and Throughput	3 Mbps data rate; throughput up to 2.17 Mbps Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric or 1306.9 kbps symmetric
Transmit Power	-6 dBm to 4 dBm (Bluetooth Class II)
Receiver Sensitivity	Better than -80 dBM at 0.1 % raw bit error rate
Power Consumption	Peak (Tx) 330 mW Peak (Rx) 230 mW Sleep <17 mW

Antenna	Internally integrated within module
Range	Up to 33 ft (10 m)
Electrical Interface	USB 2.0 compliant Microsoft Windows Plug and Play compliant
Bluetooth Software Supported	Broadcom Bluetooth for Windows Microsoft Windows Bluetooth Software
Link Topology	Point to Point, Multipoint Pico Nets up to 7 slaves
Security	Full support of Bluetooth Security Provisions
Power Management	Microsoft Windows ACPI, and USB Bus Support Self configurable to optimize power conservation in all operating modes, including Standby, Hold, Park, and Sniff
Certifications	All necessary regulatory approvals for supported countries, including: FCC (47 CFR) Part 15C, Section 15.247 & 15.249 ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark
Bluetooth Profiles Supported	Generic Access Profile (GAP) Service Discovery Application Profile (SDAP) Serial Port Profile (SPP) Dial_Up Networking Profile (DUN) Generic Object Exchange Profile (GOEP) Object Push Profile (OPP) File Transfer Profile (FTP) Synchronization Profile (SYNC) Hard Copy Cable Replacement (HCRP) Personal Area Networking Profile (PAN) Human Interface Device Profile (HID) Generic Audio/Video Distribution Profile (GAVDP) Advanced Audio/Video Distribution Profile (A2DP) FAX Profile (FAX) Basic Imaging Profile (BIP) Headset Profile (HSP) Hands Free Profile (HFP) Basic Printing Profile (BPP) VDP (Video Distribution Profile) AVRCP (Audio Video Remote Control Profile)

*** Wireless access point and internet service required. Availability of public wireless access points limited.**

AUDIO/MULTIMEDIA

Audio Hardware

Implementation	Realtek ALC3201-GR High Definition audio
Volume Controls	Up, down, and mute function keys
Full Duplex	Yes
Microphone In	Stereo
Headphone/Line Out	Stereo
Integrated Microphone	Yes

Technical Specifications

Audio Output Quality	**Frequency Response**	10 Hz ~ 22 KHz
	Signal to Noise Ratio	Typical 95 dB FSA (DAC)
	Total Harmonic Distortion	Typical -88 dB FS (DAC)
	Noise Floor	-110 dB
	Play/Record Sampling Rate(s)	Up to 192 KHz
	DAC	24 bits
	ADC	24 bits
Integrated Stereo Speakers	**Power Rating**	1.5 W
	Impedance	4 ohms
Multimedia		
Integrated HD Webcam	Supports videoconferencing and still image capture Improved quality for video streaming and still image capture (1280x720 resolution) Up to 30 frames/sec Fixed focus lens	

POWER

HP 45W Smart AC Adapter	**Dimensions**	3.78 x 1.95 x 0.88 in (9.6 x 4.95 x 2.24 cm)	
	Input	90 to 265 VAC	
		Input Efficiency	87% min at 115 VAC
		Input frequency range	47 to 63 Hz
		Input AC current	1.4 A at 90 VAC and maximum load
	Output	**Output power**	45W
		DC output	19.5V
		Hold-up time	5 msec at 115 VAC input
		Output current limit	<8A, Over voltage protection- 29V max automatic shutdown
	Connector	3 pin/grounded, mates with interchangeable cords	
	Environmental Design	**Operating temperature**	32° to 95° F (0° to 35° C)
		Non-operating (storage) temperature	-4° to 121° F (-20° to 85° C)
		Altitude	0 to 16,405 ft (0 to 5,000 m)
		Humidity	0% to 95%
		Storage Humidity	0% to 95%
	EMI and Safety Certifications	CE Mark - full compliance with LVD and EMC directives; Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; Reliability - failure rate of less than 0.1% annually within the first three years of operation.	

Technical Specifications

HP 65W AC Adapter	**Dimensions**	4.21 x 1.85 x 1.18 in (10.7 x 4.7 x 3.0 cm)	
	Weight	0.62 lb (280 g)	
	Input	100 to 240 VAC	
		Input Efficiency	87% min at 115 VAC
		Input frequency range	47 to 63 Hz
		Input AC current	1.7 A at 90 VAC
	Output	Output power	65W
		DC output	18.5/19.5V
		Hold-up time	5 msec at 115 VAC input
		Output current limit	<11A, Over voltage protection- 29V max automatic shutdown
	Connector	3 pin/grounded, mates with interchangeable cords	
	Environmental Design	Operating temperature	41° to 95° F (5° to 35° C)
		Non-operating (storage) temperature	-4° to 185° F (-20° to 85° C)
		Altitude	0 to 5,000 ft (0 to 1,524 m)
		Humidity	20% to 95%
		Storage Humidity	10% to 95%
	EMI and Safety Certifications	CE Mark - full compliance with LVD and EMC directives; Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; MTBF - over 200,000 hours at 25°C ambient condition.	
4-Cell (41 WHr) Lithium-Ion battery	**Cells/Type**	4-cell Lithium-Ion	
	Energy Temperature	Watt-hour capacity	41 WHr
		Operating (Charging)	32° to 113° F (0° to 45° C)
		Operating (Discharging)	14° to 140° F (-10° to 60° C)
		Non-operating	-4° to 140° F (-20° to 60° C)
	Battery Re-Charge Time	System in OFF or Standby Mode	2.5 hours
		System ON	3 to 5 hours (depending on system power consumption)
		HP Fast Charge Technology	Charges the battery up to 90% within 90 minutes when system is OFF

ENVIRONMENTAL

Eco-Label Certifications & declarations

This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- IT ECO declaration
- US ENERGY STAR®
- EPEAT < Gold> registered in the United States. See http://www.epeat.net for registration status in your country.

Technical Specifications

System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured Notebook".

Energy Consumption (in accordance with US ENERGY STAR® test method)	**115VAC, 60Hz**	**230VAC, 50Hz**	**100VAC, 60Hz**
Normal Operation (Short idle)	10.71 W	10.82 W	10.32 W
Normal Operation (Long idle)	6.52 W	6.43 W	5.64 W
Sleep	1.06 W	1.07 W	1.07 W
Off	0.33 W	0.33 W	0.33 W

Note:
Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

Heat Dissipation*	**115VAC, 60Hz**	**230VAC, 50Hz**	**100VAC, 60Hz**
Normal Operation (Short idle)	37 BTU/hr	37 BTU/hr	35 BTU/hr
Normal Operation (Long idle)	22 BTU/hr	22 BTU/hr	19 BTU/hr
Sleep	4 BTU/hr	4 BTU/hr	4 BTU/hr
Off	1 BTU/hr	1 BTU/hr	1 BTU/hr

*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)	Sound Power (L_{WAd}, bels)	Sound Pressure (L_{pAm}, decibels)
Typically Configured – Idle	2.6	25
Fixed Disk – Random writes	3.0	24

Longevity and Upgrading

This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include:

- 3 USB ports
- 1 PC card slot (type I/II)
- 1 ExpressCard/54 slot
- 1 IEEE 1394 Port
- 2 SODIMM memory slots
- Optional expansion base docking station
- 1 multi-bay II storage port

- Interchangeable HDD??

<edit list of features as required>

Spare parts are available throughout the warranty period and or for up to "5" years after the end of production.

Batteries

This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain:
Mercury greater the1ppm by weight
Cadmium greater than 20ppm by weight

Battery size: CR2032 (coin cell)
Battery type: Lithium
Battery size: 6-cell high capacity Lithium-Ion battery (optional 8 cell available)
Battery type:

Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the < gold> level, see www.epeat.net
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product contains 0% post-consumer recycled plastic (by wt.)
- This product is 94.9% recycle-able when properly disposed of at end of life.

Packaging Materials

External:	PAPER/Corrugated	415.6 g
Internal:	PLASTIC/EPE (Expanded Polyethylene)	60 g
	PLASTIC/Polyethylene low density	13.9 g

The plastic packaging material contains at least 50% recycled content.
The corrugated paper packaging materials contains at least 70% recycled content.

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants – may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes

- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

Packaging Usage

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

Technical Specifications

Hewlett-Packard Corporate Environmental Information

For more information about HP's commitment to the environment:

Global Citizenship Report
http://www.hp.com/hpinfo/globalcitizenship/qcreport/index.html
Eco-label certifications
http://www8.hp.com/us/en/hp-information/environment/ecolabels.html
ISO 14001 certificates:
http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf
and
http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf

COUNTRY OF ORIGIN

China

Options and Accessories (sold separately and availability may vary by country)

NOTE: Options/capabilities listed in the QuickSpecs represent those capabilities available through Base Units or Build to Order configurations. The various product features and capabilities will vary in terms of configurable vs. aftermarket options (AMOs). There may be options and capabilities available through CTO that are not available as AMOs.

Type	Description	Part #
Docking	HP 3005pr USB 3.0 Port Replicator	H1L08AA#xxx
	HP 2005pr USB 2.0 Port Replicator	H1L07AA#xxx
	HP 3001 USB 3.0 Port Replicator	F3S42AA#xxx
	HP Display and Notebook Stand	AW662AA
Input/Output	HP Stylish USB Keyboard and Mouse	H4B80AA#xxx
	HP Stylish Wireless Keyboard and Mouse	H4B79AA#xxx
	HP Comfort Grip Wireless Mouse	H2L63AA
	HP X4000b Bluetooth Mouse	H3T50AA#xxx
	HP 3-Button USB Laser Mouse	H4B81AA
	HP USB Optical Travel mouse	RH304AA
	USB Graphics Adapter (DBU PL)	NL571AA
Power	HP 45W Smart AC Adapter (4.5mm)	H6Y88AA
	HP 65W Smart AC Adapter (4.5mm)	H6Y89AA
	HP 90W Smart AC Adapter (4.5mm)	H6Y90AA
Security	HP UltraSlim Keyed Cable Lock	H4D73AA
Storage - External Storage	HP External USB Optical Drive	F2B56AA
Other	HP HDMI to VGA Adapter	F5A28AA
Monitors	HP EliteDisplay E271i 27-inch IPS LED Monitor	D7Z72AA/A8/AS/AT
	HP EliteDisplay E231 23-inch LED Monitor	C9V75AA/A8/AS/AT
	HP EliteDisplay E201 20-inch LED Monitor	C9V73AA/A8/AS/AT
	HP ProDisplay P221 21.5" LED Monitor	C9E49AA/A8/AS/AT
	HP ProDisplay P201 20" LED Monitor	C9F26AA/A8/AS/AT

Copyright © 2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Radeon and Athlon are registered trademarks or trademarks of AMD Corporation in the U.S. and/or other countries. Bluetooth is a trademark owned by its proprietor and used by Hewlett-Packard Company under license. ENERGY STAR is a registered mark owned by the U.S. government. Microsoft and Windows are U.S. registered trademarks of Microsoft Corporation.

Options and Accessories (sold separately and availability may vary by country)

Summary of Changes

Date of change:	Version History:		Description of change:
June 10, 2014	From vApr'14 to vJun'14	Added	Environmental data, change log, cNumber on footer